



General Description

Junckers PRELAK is a fast drying, water-based primer to be used in combination with water-based floor finishing products.

Junckers PRELAK provides a water-based solution for priming of floors with wood species sensitive to changes in humidity.

Technical Data

Product:	Water-based acrylic primer.
Package sizes:	5 litre and 10 litre.
Appearance:	Creamy/milky. Dries up to a clear film. Provides a lighter appearance than solvent-based primers.
Coverage:	8 m ² per litre.
Application tools:	Short hair roller.
Substrate temperature:	Minimum 15°C.
Dilution:	Delivered ready for use. Dilution is not recommended.
Drying time:	Approx. 1-2 hours at 20°C.
Cleaning of tools:	Soap and water immediately after use. Junckers Thinner 006 after drying.
Storage:	Lasts for 2 years if unopened and stored at 20°C. Not to be exposed to temperatures below 0°C.

System Recommendations

High traffic areas:	1 coat Junckers PRELAK 8 m ² /ltr.
	+ 2 coats Junckers High Performance Commercial 10m ² ltr.
	or
	1 coat Junckers PRELAK 8 m ² /ltr.
	+ 2 coats Junckers STRONG 10m ² ltr.
Low traffic areas:	1 coat Junckers PRELAK 8 m ² /ltr.
	+ 2 coat Junckers STRONG 8 m ² /ltr.
	or
	1 coat Junckers PRELAK 8 m ² /ltr.
	+ 2 coat Junckers PRO FINISH 10 m ² /ltr.
Sport areas:	1 coat Junckers PRELAK 8 m ² /ltr.
	+ 2 coats Junckers HP SPORT 10-12 m ² /ltr.
	or
	1 coat Junckers PRELAK 8 m ² /ltr.
	+ 2 coat Junckers HP ONE 10-12 m ² /ltr.

Directions for Use

Untreated/sanded floors

The surface should be clean, dry and free from dust, wax, grease, polish etc.. Machine sand the surface to remove dirt and irregularities. The last sanding, before applying **Junckers PRELAK** should be carried out by using sandpaper grit 100-120. Apply **Junckers PRELAK** as an even coat using a clean, shorthaired roller or applicator. Do not apply by spraying. When the primer is dry, sand with sandpaper grit 150-180 or a black screening pad.

Previously lacquered floors:

Machine sand before applying **Junckers PRELAK**. Use grit 24-36 to strip old coats. Then remove abrasion marks with grit 60-80. Finally, use grit 100-120 to obtain a completely smooth surface. Vacuum sanding dust and prime the floor as described under “**Untreated/ sanded floors**”.

Important!

Before use of the product, read the label on the container carefully and observe the advised precautionary safety measures.

Important!

Water-based products have a certain gluing effect and are therefore recommended to be used in rooms with a stable humidity. This means that the humidity range from highest to lowest relative humidity should not vary more than 30% during the year.

Important!

Don't apply by pouring out the lacquer. Apply using recommended tools.

Important!

Stir well before use.

Further information

Products:

F 3.6 - **Junckers HP ONE**
 F 4.2 - **Junckers PRO FINISH**
 F 5.1 - **Junckers STRONG**
 F 6.5 - **Junckers Thinner 006**
 F 8.2 - **Junckers HP SPORT**
 F 8.5 - **Junckers High Performance Commercial**